

**In accordance with Annex III of Regulation (EU) No 305/2011  
(Construction Products Regulation)  
CT1 COLOURS**

No: UKDOP2022-1-CT1

**1. Unique identification code of the product - type:**

C-TEC CT1 COLOURS (excluding Clear & Silver)

**2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):**

For batch number: see product packaging.

**3. Intended use or uses of the construction product, in accordance with applicable harmonised technical specification, as foreseen by the manufacturer:**

EN15651-1: F-EXT-INT-CC (CLASS 20HM): Sealant for façade elements

EN15651-3: S: Sealant for sanitary Joints

EN15651-4: PW (CLASS 20HM): Sealant for Pedestrian Walkways

**4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):**

C-TEC N.I. Limited, Unit 6 Ashtree Enterprise Park,  
Newry, Co. Down, BT34 1BY, Northern Ireland.

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the task specified in Article 12 (2):**

Not Applicable.

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

System 3

System 3 for reaction to fire

**7. In case of declaration of performance concerning a construction product covered by a harmonised standard:**

EN15651-1: F-EXT-INT-CC

EN15651-3

EN15651-4: PW

Approved Body 4Ward Testing Ltd, identification number 2538, performed initial type testing under system 3 and issued a test report

**8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

Not Applicable.

## 9. Declared Performance

**EN 15651-1: F-EXT-INT-CC**  
**Non-structural sealant for joints only on the internal side of façade elements**  
**Pre-Conditioning: Method B (according to ISO 8340)**  
**Substrate: Glass – without primer**  
**Aluminium - without primer**  
**Mortar – with primer**

Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (EN13501)	Class E	
Release of Chemicals dangerous to the environment and health	NPD See product safety data sheet	
Water Tightness & Air Tightness as determined by:		
Resistance to flow	≤ 3mm	EN 15651-1: 2012
Loss of volume	≤ 10%	EN 15651-1: 2012
Tensile properties: elongation at break	NF	EN 15651-1: 2012
Durability	Pass	EN 15651-1: 2012

**EN 15651-3: S**  
**Non-structural sealant for sanitary joints**  
**Pre-Conditioning: Method B (according to ISO 8340)**  
**Substrate: Glass – without primer**  
**Aluminium - without primer**  
**Mortar – with primer**

Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (EN13501)	Class E	
Release of Chemicals dangerous to the environment and health	NPD See product safety data sheet	
Water Tightness & Air Tightness as determined by:		
Resistance to flow	≤ 3mm	EN 15651-1: 2012
Loss of volume	≤ 20%	EN 15651-1: 2012
Tensile properties: elongation at break	NF	EN 15651-1: 2012
Microbiological Growth	SX3	EN 15651-1: 2012
Durability	Pass	EN 15651-1: 2012

**EN 15651-4: PW EXT – INT CC**  
**Non-structural sealant for use in pedestrian walkways**  
**Pre-Conditioning: Method B (according to ISO 8340)**  
**Substrate: Glass – without primer**  
**Aluminium - without primer**  
**Mortar – with primer**


Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (EN13501)	Class E	
Release of Chemicals dangerous to the environment and health	NPD See product safety data sheet	
Water Tightness & Air Tightness as determined by:		
Resistance to flow	≤ 3mm	EN 15651-1: 2012
Loss of volume	≤ 10%	EN 15651-1: 2012
Tensile properties: elongation at break	NF	EN 15651-1: 2012
Tear Resistance	NF	EN 15651-1: 2012
Durability	Pass	EN 15651-1: 2012

**Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:**

Not relevant.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by,



Jimmy Walsh  
 Managing Director  
 C-TEC N.I Limited  
 August 2022

**UK  
CA**  
2538

22

C-TEC N.I. Limited, Unit 6 Ashtree Enterprise Park,  
Newry, Co. Down, BT34 1BY, Northern Ireland

Reference No: UKDOP2022-1-CT1 (COLOURS)

**CT1 – COLOURS**

EN 15651-1: F-EXT-INT-CC

Pre-Conditioning: Method B.

Substrate: Glass – without primer

Aluminium – without primer

EN 15651-1: F-EXT-INT-CC

**Façade Sealant For Interior And Exterior Application**

REACTION TO FIRE: CLASS E; RESISTANCE TO FLOW  $\leq$  3MM;  
LOSS OF VOLUME  $\leq$  10%; ELONGATION AFTER IMMERSION IN  
WATER: NO FAILURE; DURABILITY: PASS

EN 15651-3: S

**Non-Structural Sealant For Sanitary Joints**

REACTION TO FIRE: CLASS E; RESISTANCE TO FLOW  $\leq$  3MM;  
LOSS OF VOLUME  $\leq$  20%; ELONGATION AFTER IMMERSION IN  
WATER: NO FAILURE; MICROBIOLOGICAL GROWTH: 3;  
DURABILITY: PASS

EN 15651-4: PW-EXT-CC

**Non-Structural Sealant For Use In pedestrian Walkways**

REACTION TO FIRE: CLASS E; RESISTANCE TO FLOW  $\leq$  3MM;  
LOSS OF VOLUME  $\leq$  10%; ELONGATION AFTER IMMERSION IN  
WATER: NO FAILURE; TEAR RESISTANCE: NO FAILURE;  
DURABILITY: PASS