CONSTANT VOLTAGE LONG & SLIM DRIVER 30W 24VDC IP20 NON-DIMM 180-264V INPUT INTEGRAL

ILDRCVA065



The Integral 30W constant voltage Long & Slim LED driver operates 200-240VAC input range. The LED driver provides 24V constant voltage and up to 1.25A of output current for a 30W maximum output power. Integral LED drivers deliver high reliability and efficiency >= 82% and are fully compatible with 24V constant voltage LED lighting systems. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Barcode:	5055788254812
Quick Order Code:	352960
Category:	Drivers
Range Name:	Non-Dimmable
Product Type:	Constant Voltage
Market Segment:	Commercial indoor, Residential indoor, Commercial outdoor (with appropriate outdoor fitting), Residential outdoor (with appropriate outdoor fitting)
Warranty (Years):	3

Physical Data

Product Length (mm):	251
Product Depth (mm):	16
Product Width (mm):	30
Product Weight (g):	135
Material:	Plastic Shell
Placement / Application:	Indoor LED Lighting, Outdoor LED Light (with appropriate outdoor fitting)

Electrical Data

Power (W):	30
Power Consumption (W) :	30
Power Factor:	0.9
Voltage (V):	24
Voltage Range (v):	200-240
Input Current (A):	0.22

Input Voltage (V):	200-240
Output Current (mA):	1250
Dimming:	Non-Dimmable
Electric Current:	AC
Protection Function:	Short Circuit Protection, Overload Protection, Overheat Protection
EN:	EN61000-3-2, EN55015, EN61547
LVD Certified:	Yes

Light Data

Frequency Range (Hz):	50/60

Environment

EN:	EN61000-3-2, EN55015, EN61547
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Barcode:	5055788254812
Single box qty:	1
Package Weight (g):	140
Package Length (mm):	263
Package Width (mm):	38
Package Depth (mm):	22
Outer Carton Barcode:	5055788255130
Qty per Outer Carton:	100
Outer Carton Length (mm):	400
Outer Carton Width (mm):	268
Outer Carton Depth (mm):	235

Integral-led.com - Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE